

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A commutator arrangement for a small electric motor, comprising:

a capacitor ring disk consisting of several capacitor elements, said capacitor ring disk comprising a dielectric first ring disk (RS) on whose upper side several sector-shaped electrode layers (6) are positioned, each of the electrode layers (6) being electrically conductively connected with a commutator segment (13), and wherein counter electrodes of the capacitor elements are provided on an underside of the ring disk (RS), which is located opposite the upper side of the ring disk (RS),

wherein a single underlying counter electrode layer (4) is provided, said counter electrode layer (4) underlies and almost covers the electrode layers (6) so that the counter electrodes of all capacitor elements have the same potential.

2. (Previously Presented) The commutator arrangement as defined in claim 1, wherein a plurality of capacitor ring disks are laminated on top of one another with a dielectric layer (15) disposed between adjacent capacitor ring disks .

3. (Previously Presented) The commutator arrangement as defined in claim 2, wherein the capacitor ring disks are laminated one on top of the other so that the electrode layers (6) are essentially located congruently over each other.

4. (Previously Presented) The commutator arrangement as defined in

claim 2, wherein the capacitor elements created by the electrode layers (6) stacked on top of each other are contacted together to create a capacitive element and are each connected with a commutator segment (13).

5. (Previously Presented) The commutator arrangement as defined in claim 2, wherein the electrode layers (6) placed on top of one another are contacted with each other on an exterior circumferential surface of the first ring disk (RS).

6. (Previously Presented) The commutator arrangement as defined in claim 1, wherein the counter electrode layer (4) is round and extends up to an interior circumference of the first ring disk (RS).

7. (Previously Presented) The commutator arrangement as defined in claim 1, wherein the counter electrode layer (4) is formed as resistance layer with a resistance in the range from 0.1 Ω to 1 K Ω .

8. (Currently Amended) The commutator arrangement as defined in claim 1, wherein at least one inductor is connected before or after each capacitor element ~~or each capacitive element in series~~.

9. (Currently Amended) The commutator arrangement as defined in claim 1, wherein at least one discrete inductor is connected before or after each capacitor element ~~or each capacitive element in series~~.

10. (Previously Presented) The commutator arrangement as defined in claim 1, further comprising a second ring disk made of a highly permeable magnet material, said second ring disk being provided for which each of the inductors is formed by a conductive structure placed thereon, and wherein each of the capacitances is electrically conductively connected with one of the inductors.

11. (Currently Amended) The commutator arrangement as defined in

claim 1, wherein at least one resistance is connected before or after each capacitor element ~~or each capacitance~~ in series.

12. (Previously Presented) The commutator arrangement as defined in claim 11, wherein the resistance has a non linear U/I characteristic curve.

13. (Previously Presented) The commutator arrangement as defined in claim 11, wherein the resistances are designed in one piece in the form of a third ring disk or as a further resistance layer placed on a ring disk or on the electrode layer (6) or the counter electrode layer (4).

14. (Currently Amended) The commutator arrangement as defined in claim 11, wherein ~~the~~ a second and/or ~~the~~ a third ring disk (16) or resistance layer form a laminate (L) with the capacitor ring disk(s).

15. (Previously Presented) The commutator arrangement as defined in claim 14, wherein a supporting disk (11) made of ceramic is provided for the retention of the capacitor or the laminate (L).

16. (Previously Presented) The commutator arrangement as defined in claim 14, wherein the capacitor ring disk(s) or the laminate (L) are connected with a commutator sleeve (12) supporting the commutator segments (13).

17. (Currently Amended) The commutator arrangement as defined in claim 14, wherein the capacitor ring ~~disk(s)~~ disks or the laminate (L) is surrounded by the commutator segments (13).

18. (Previously Presented) A small electric motor with a shaft and a commutator arrangement mounted thereon as defined in claim 1.